

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION
AND COMPANY / UNDERTAKING**

| | |
|-------------------------------|--|
| Product Name | KLEA™ 134a |
| REACH Registration No. | 01-2119459374-33-0000 |
| Manufacturer | Mexichem UK Limited PO Box 13 The Heath Runcorn Cheshire WA7 4QX Tel: +44(0) 1928 511192 Fax: +44(0) 1928 517592 E-Mail: info@mexichem.com |
| Emergency Phone No. | IN AN EMERGENCY DIAL 999 (UK Only) For specialist advice in an emergency telephone +44(0) 1928 572000 |
| Use | Subject to Member State regulations, applicable uses are: refrigerant , blowing agent , propellant , solvent |

2. HAZARDS IDENTIFICATION

Low acute toxicity. High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.
Liquid splashes or spray may cause freeze burns to skin and eyes.

EC Classification

| | |
|---|--------------------------------------|
| EC Directive 67/548/EEC: | Not classified. |
| Regulation (EC) No. 1272/2008 (CLP). | Gases under pressure - Liquefied gas |

Label elements

| | |
|----------------------------|---|
| Hazard statement(s) | H280: Contains gas under pressure; may explode if heated. |
| Signal word(s) | Warning |
| Hazard pictogram(s) | |



GHS04

| | |
|-----------------------------------|---|
| Precautionary statement(s) | P410 + P403: Protect from sunlight. Store in a well-ventilated place. |
|-----------------------------------|---|

3. COMPOSITION / INFORMATION ON INGREDIENTS

| | |
|--------------------------|--|
| Alternative names | 1,1,1,2-tetrafluoroethane (HFC 134a) R 134a |
|--------------------------|--|

HAZARDOUS INGREDIENT(S)

| Hazardous ingredient(s) | %(w/w) | CAS No. | EC No. | Hazard symbol(s) and hazard statement(s) |
|--------------------------------------|--------|-------------|-----------|--|
| 1,1,1,2-tetrafluoroethane (HFC 134a) | 100 | 000811-97-2 | 212-377-0 | GHS04 H280 |

4. FIRST AID MEASURES



The first aid advice given for skin contact, eye contact, and ingestion is applicable following exposures to the liquid or spray. See also section 11.

| | |
|----------------------------------|---|
| Inhalation | Remove patient from exposure, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In the event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention. |
| Skin Contact | Thaw affected areas with water. Remove contaminated clothing. Caution: clothing may adhere to the skin in the case of freeze burns. After contact with skin, wash immediately with plenty of warm water. If irritation or blistering occur obtain medical attention. |
| Eye Contact | Immediately irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes. Obtain immediate medical attention. |
| Ingestion | Unlikely route of exposure. Do not induce vomiting. Provided the patient is conscious, wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain immediate medical attention. |
| Further Medical Treatment | Symptomatic treatment and supportive therapy as indicated. Adrenaline and similar sympathomimetic drugs should be avoided following exposure as cardiac arrhythmia may result with possible subsequent cardiac arrest. |

5. FIRE-FIGHTING MEASURES

| | |
|---|---|
| General | HFC 134a is not flammable in air under ambient conditions of temperature and pressure. Certain mixtures of HFC 134a and air when under pressure may be flammable. Mixtures of HFC 134a and air under pressure should be avoided. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions. Thermal decomposition will evolve very toxic and corrosive vapours. (hydrogen fluoride) Containers may burst if overheated. |
| Extinguishing media | As appropriate for surrounding fire. Keep fire exposed containers cool by spraying with water. |
| Fire Fighting Protective Equipment | A self contained breathing apparatus and full protective clothing must be worn in fire conditions. See Also Section 8 |

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------|---|
| Personal Protection | Ensure suitable personal protection (including respiratory protection) during removal of spillages. See Also Section 8 |
| General | Provided it is safe to do so, isolate the source of the leak. Allow small spillages to evaporate provided there is adequate ventilation. Large spillages: Ventilate area. Contain spillages with sand, earth or any suitable adsorbent material. Prevent liquid from entering drains, sewers, basements and workpits since the vapour may create a suffocating atmosphere. |

7. HANDLING AND STORAGE

Handling

Avoid inhalation of high concentrations of vapours. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Atmospheric concentrations well below the occupational exposure limit can be achieved by good occupational hygiene practice.

The vapour is heavier than air, high concentrations may be produced at low levels where general ventilation is poor, in such cases provide adequate ventilation or wear suitable respiratory protective equipment with positive air supply.

Avoid contact with naked flames and hot surfaces as corrosive and very toxic decomposition products can be formed.

Avoid contact between the liquid and skin and eyes.

Avoid venting to atmosphere.

The fluorinated greenhouse gas R 134a may be supplied in returnable containers (drums/cylinders). The container contains fluorinated greenhouse gases covered by the Kyoto Protocol. The fluorinated greenhouse gases in containers may not be vented to the atmosphere. Regulation (EC) No. 842/2006 of the European Parliament and the Council on certain fluorinated greenhouse gases.

Process Hazards

Liquid refrigerant transfers between refrigerant containers and to and from systems can result in static generation. Ensure adequate earthing. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.

Care must be taken to mitigate the risk of developing high pressures in systems caused by a temperature rise when liquid is trapped between closed valves or in cases where containers have been overfilled.

Storage

Keep in a well ventilated place away from fire risk and avoid sources of heat such as electric or steam radiators.

Avoid storing near to the intake of air conditioning units, boiler units and open drains.

Specific use

Subject to Member State regulations, applicable uses are: refrigerant , blowing agent , propellant , solvent

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

General

Wear suitable protective clothing, gloves and eye/face protection. Wear thermal insulating gloves when handling liquefied gases. In cases of insufficient ventilation, where exposure to high concentrations of vapour is possible, suitable respiratory protective equipment with positive air supply should be used.



Eye Protection



Gloves

Occupational Exposure Limits

| Occupational Exposure Limits | CAS No. | LTEL (8 hr TWA ppm) | LTEL 8 hr TWA mg/m ³ | STEL (ppm) | STEL mg/m ³ | Note: |
|--------------------------------------|-------------|------------------------------|--|---------------|---------------------------|-------|
| 1,1,1,2-Tetrafluoroethane (HFC 134a) | 000811-97-2 | 1000 | 4240 | - | - | WEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------|---|
| Form | liquefied gas |
| Colour | colourless |
| Odour | slight ethereal |
| Solubility (Water) | slightly soluble |
| Solubility (Other) | Soluble in: alcohols , chlorinated solvents , polyethylene glycol |
| Boiling Point (° C) | -26.2 |
| Melting Point (° C) | -101 |
| Vapour Density (Air=1) | 3.66 at normal boiling point |
| Vapour Pressure (mm Hg) | 4270 at 20 ° C |
| Specific Gravity | 1.22 at 20 ° C |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Hazardous Reactions | Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions. Incompatible materials: finely divided metals , magnesium and alloys containing more than 2% magnesium . Can react violently if in contact with alkali metals and alkaline earth metals - sodium , potassium , barium |
| Hazardous Decomposition Product(s) | hydrogen fluoride by thermal decomposition and hydrolysis. |

11. TOXICOLOGICAL INFORMATION

| | |
|--------------------|--|
| Inhalation | LC50 (rat) (4 hrs) > 500000 ppm (2080000 mg/m3) High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation. |
| Skin Contact | Liquid splashes or spray may cause freeze burns. Unlikely to be hazardous by skin absorption. |
| Eye Contact | Liquid splashes or spray may cause freeze burns. |
| Ingestion | Highly unlikely - but should this occur freeze burns will result. |
| Long Term Exposure | A lifetime inhalation study in rats has shown that exposure to 50000ppm resulted in benign tumours of the testis. The increased tumour incidence was observed only after prolonged exposure to high levels, and is considered not to be of relevance to humans occupationally exposed to HFC 134a at or below the occupational exposure limit. |

12. ECOLOGICAL INFORMATION

| | |
|-------------------------------------|--|
| Environmental Fate and Distribution | High tonnage material produced in wholly contained systems. High tonnage material used in open systems. Gas. |
| Persistence and Degradation | Decomposed comparatively rapidly in the lower atmosphere (troposphere). Atmospheric lifetime is 14 years. Products of decomposition will be highly dispersed and hence will have a very low concentration. Does not influence photochemical smog (i.e. is not a VOC under the terms of the UNECE agreement). Does not deplete ozone. Has a Global Warming Potential (GWP) of 1300 (relative to a value of 1 for carbon dioxide at 100 years) according to Annex I of Regulation 842/2006 on certain fluorinated greenhouse gases. Values in Annex I are taken from the third assessment report (TAR) of the Intergovernmental Panel on Climate Change (2001 IPCC GWP values). United Nations Framework Convention on Climate Change (UNFCCC) reporting GWP is 1300. |

SAFETY DATA SHEET

Effect on Effluent Treatment

Discharges of the product will enter the atmosphere and will not result in long term aqueous contamination.

13. DISPOSAL CONSIDERATIONS

Recommended:

Best to recover and recycle. If this is not possible, destruction is to be in an approved facility which is equipped to absorb and neutralise acid gases and other toxic processing products.

14. TRANSPORT INFORMATION

Hazard Label



| | |
|-------------------------------------|--|
| Road/Rail | |
| UN No. | 3159 |
| ADR/RID Class | 2.2 |
| ADR/RID Proper Shipping Name | 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R 134a) |
| SEA | |
| IMDG Class | 2.2 |
| Marine Pollutant | Not classified as a Marine Pollutant |
| AIR | |
| ICAO/IATA | 2.2 |

15. REGULATORY INFORMATION

European Regulations

Special Restrictions:

The fluorinated greenhouse gas R 134a may be supplied in returnable containers (drums/cylinders). The container contains fluorinated greenhouse gases covered by the Kyoto Protocol. The fluorinated greenhouse gases in containers may not be vented to the atmosphere.

Regulation (EC) No. 842/2006 of the European Parliament and the Council on certain fluorinated greenhouse gases.

Directive 2006/40/EC of the European Parliament and the Council relating to emissions from air-conditioning systems in motor vehicles and amending Council Directive 70/156/EC.

16. OTHER INFORMATION

This data sheet was prepared in accordance with Regulation (EC) No. 1907/2006.

Information in this publication is believed to be accurate and is given in good faith, but it is for the User to satisfy itself of the suitability for its own particular purpose. Accordingly, Mexichem UK Limited gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed. Mexichem Fluor™ is a trademark, the property of Mexichem SAB de C.V. KLEA™ is a trademark, the property of Mexichem SAB de C.V. Mexichem UK Limited is Registered in England No 7088219. Registered Office The Heath Business & Technical Park, Runcorn, Cheshire WA7 4QX. © Mexichem UK Limited 2010.

SAFETY DATA SHEET

Glossary

WEL: Workplace Exposure Limit (UK HSE EH40)
COM: The company aims to control exposure in its workplace to this limit
TLV: The company aims to control exposure in its workplace to the ACGIH limit
TLV-C: The company aims to control exposure in its workplace to the ACGIH Ceiling limit
MAK: The company aims to control exposure in its workplace to the German limit
Sk: Can be absorbed through skin
Sen: Capable of causing respiratory sensitisation
Bmgv: Biological monitoring guidance value (UK HSE EH40)

Hazard statement(s)

H280: Contains gas under pressure; may explode if heated.